

TECHNICAL DATA SHEETS

PERMOGLAZE XTREME WHITE

DESCRIPTION	<p>Permoglaze Xtreme White is a high-quality water-based paint with high viscosity, spreading rate, opacity and whiteness. Offers good application properties after a dilution up to 30%. Suitable for walls and ceilings on interior and exterior surfaces. Permoglaze Xtreme White is compliant with the Mauritius Standards Bureau Ecolabel Standard.</p>		
CHARACTERISTICS	<ul style="list-style-type: none"> • Ecological • Low odour • High spreading rate • Outstanding opacity • Good flow properties • Excellent whiteness • Hard-wearing and long lasting • High viscosity • Quick drying • Interior and exterior use 		
COMPOSITION	<p>Emulsion paint based on a high durability polymeric medium and incorporating the highest quality pigments specially selected for their performance.</p>		
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Surfaces must be free of dirt, dust, grease, oil and loose paint. • Surfaces infected by mould or algae growth must be treated with Permoglaze Biocidal Wall Wash followed by Permoglaze Fungicidal Treatment. • Bare and porous concrete surfaces must be washed thoroughly with water then primed with 1 coat of Permoglaze Aqua Prime for maximum opacity. • Leave to dry before applying Permoglaze Xtreme White. • 2-3 coats of Permoglaze Xtreme White are recommended for good performance. 		
APPLICATION	Method	Brush, Roller, Airless Spray	
	Thinning	Water	
	Dilution (Brush & Roller)	1 st Coat	Dilution volume ratio of 5 parts of paint to 1½ part of water (or dilute with 30% water).
		2 nd & 3 rd Coat	Dilution volume ratio of 5 parts of paint to 1 part of water. (or dilute with 20% water).
	Dilution (Airless Spray)	1 st Coat	Dilution volume ratio of 5 parts of paint to 1 part of water (or dilute with 20% water).
		2 nd & 3 rd Coat	Dilution volume ratio of 5 parts of paint to ½ part of water (or dilute with 10% water).
	Cleaning	Water	

TECHNICAL DATA SHEETS

PERMOGLAZE XTREME WHITE

PRODUCT INFORMATION	Finish	Matt
	Shades	White
	Spreading Rate	9-12m ² /liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode
	VOC	Limit for this product: 10 g/L. This product contains less than 1.0g/L VOC.
	SVOC	Limit for this product: 30-40 g/L. This product contains less than 7.1g/L VOC.
	Drying Time	Touch Dry 30 minutes at 25°C Hard Dry 1-3 hours at 25°C
PRECAUTIONS	<ul style="list-style-type: none"> • The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. • Not recommended for ceilings as it may show the imperfections of the surface. 	
PACKAGING	Available in 1,5, 10 & 20 litres	
STORAGE	Store in a cool, dry and well-ventilated place.	
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none"> • Handle with care • Ensure good ventilation during application. • In case of insufficient ventilation during painting, wear suitable respiratory equipment. • Avoid contact with skin and eyes. • If contact with skin occurs, wash well with soap and water • In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. • Keep out of reach of children. • Do not use empty paint containers for storing foodstuffs. • Do not throw paint containers or contents in the waterways or environment. • Contains no added Lead/Mercury/Nickel/Cadmium. 	

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.